

# ACCESSORIES

## DM BTH HYBRID

BTH II GSM II  
2 GSM Lines

DM BTH Line are advanced telephone Hybrids to manage high-quality communications between the studio and its listeners.

All equipments are 1 Unit Rack and with easy and intuitive front Send and Receive adjustments. High audio quality with balanced IN/OUT, ADJ Send and Receive level.



## DM 1200 LED LIGHT

The DM 1200 LED Light features digital dimming, so that , color-rendering index and color temperature won't change or suffer from color distortion. You can control the light using a DMX control. It includes power adapter, 4 barndoors, diffusion filter and bag.

Technical Features: IN/OUT DMX - 4 digital signal displays, AC 110V / 220V, 50 – 60Hz. Power LED 1200 eq. 80W. CRI>90. Constant current frequency: 660KHz. Dimming frequency: 16.6 KHz. PWM Dimming.





## DM O'CLOCK

It's a professional clock that can display different information at the same time, the synchronisation is done thanks to Internet or GPS time server.

DM O'Clock can also work manually in stand alone mode.

- View Up to three Status with "ON" mode Time Calculation if activated
- Fully remotable from any device with a browser
- It receives commands via custom web based API
- Allows the display of a 1 line scrollable text
- Management of emergency alert messages
- It allows remote viewing of the screen from any browser

## DM ON AIR LIGHT

Professional ON AIR Sign for Television, Radio, Music & Broadcast Facilities. Polycarbonate Graphic Panel, Laser cut. RJ45 connection, operating and Output Voltage 12 Vdc. Current 330 mA. AC/DC Single Output Wall Mount Adaptor. Input Voltage 100-240Vac.

Product Dimensions: Width: 38,3cm Depth: 4,2 cm Height: 13,5 cm 1 Kg.

### DM BROADCAST S.R.L

Via Degli Orti, 1 | Funo di Argelato  
Bologna | Italy | [www.dmbroadcast.it](http://www.dmbroadcast.it)  
Ph. +39 051 817657 | [info@dmbroadcast.it](mailto:info@dmbroadcast.it)

